





<b>MATERIAL:</b> 1.2 mm Steel / Powder Coating RAL7035 / 9005				
<b>Load Capacity:</b> 2000kg				
<b>DIMENSIONS(mm)</b>				
<b>SIZE</b>	<b>W</b>	<b>H</b>	<b>D</b>	<b>X</b>
MR.GTN12U88.XX	800	671	800	542
MR.GTN16U88.XX	800	849	800	772
MR.GTN20U88.XX	800	1027	800	950
MR.GTN22U88.XX	800	1116	800	1039
MR.GTN26U88.XX	800	1294	800	1217
MR.GTN32U88.XX	800	1560	800	1483
MR.GTN36U88.XX	800	1738	800	1661
MR.GTN40U88.XX	800	1916	800	1839
MR.GTN42U88.XX	800	2005	800	1928
MR.GTN46U88.XX	800	2183	800	2106

PERFORATED DOOR OPTIONS	
<b>XX_PRF63</b>	FRONT SINGLE PERFORATED-REAR DOUBLE PERFORATED
<b>XX_OPRF63</b>	FRONT SINGLE PERFORATED-REAR SOLID METAL(W600 SINGLE / W800 DOUBLE)
<b>XX_ODPRF63</b>	FRONT DOUBLE PERFORATED-REAR SOLID METAL(W600 SINGLE / W800 DOUBLE)
<b>XX_APRF63</b>	REAR SINGLE PERFORATED-FRONT GLASS (W600 SINGLE / W800 DOUBLE)
<b>XX_ADPRF63</b>	REAR DOUBLE PERFORATED-FRONT GLASS (W600 SINGLE / W800 DOUBLE)
<b>XX_OADPRF63</b>	FRONT DOUBLE PERFORATED-REAR DOUBLE PERFORATED
<b>XX_OAPRF63</b>	FRONT SINGLE PERFORATED-REAR SINGLE PERFORATED
<b>XX_ODAPRF63</b>	FRONT DOUBLE PERFORATED- REAR SINGLE PERFORATED
<b>XX_NOPRF63</b>	ANGLED FRONT FERFORATED-REAR SOLID METAL (W600 SINGLE / W800 DOUBLE)
<b>XX_NPRF63</b>	ANGLED FRONT FERFORATED-REAR DOUBLE PERFORATED



